ELITE SERIES N TOPCON TECHNOLOGY

BiN-05-415 to BiN-05-440 Framed Dual Glass Bifacial module





Highest reliability & enhanced crack tolerance MBB module



Sustain heavy snow & wind loads (5400 Pa & 2400 Pa)



Best in class thermal coefficients




Highest commercial gains, lower LCOE



Better weak light performance



Excellent PID resistance











IEC 61215, IEC 61730 UL 61730-1, UL 61730-2

I-V VARIATION WITH TEMPERATURE



 $\label{thm:consult} \mbox{The Graphs are for reference purpose only. Please consult Waaree technical team for further clarifications.}$



ELITE SERIES N TOPCON TECHNOLOGY

BiN-05-415 to BiN-05-440

Framed Dual Glass Bifacial module



ELECTRICAL CHARACTERISTICS

	Models	Pmax (W)		Vmp (V)		Imp (A)		Isc (A)		Voc (V)		Module Eff. (%)
		STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	Module Ell. (90)
	BiN-05-415	415	313.3	31.42	29.44	13.21	10.65	14.02	11.30	37.99	36.09	21.25
	BiN-05-420	420	317.1	31.63	29.63	13.28	10.70	14.09	11.36	38.10	36.19	21.51
	BiN-05-425	425	320.9	31.84	29.83	13.35	10.76	14.16	11.41	38.26	36.35	21.76
	BiN-05-430	430	324.7	32.04	30.02	13.42	10.82	14.23	11.47	38.42	36.50	22.02
	BiN-05-435	435	328.4	32.25	30.21	13.49	10.87	14.30	11.53	38.58	36.65	22.27
	BiN-05-440	440	332.2	32.42	30.38	13.57	10.94	14.38	11.59	38.83	36.88	22.53

^{*}Standard Test Conditions (STC) - 1000 W/m2 irradiance, Air Mass 1.5 and 25°C cell temperature. Nominal Operating Cell Temperature (NOCT) - 800 W/m2 irradiance, Air Mass 1.5, Ambient temperature 20°C and Wind speed 1 m/s. Average power reduction of 4.5% at 200 W/m2 as per IEC 60904-1. Measuring Uncertainty ± 3%.


System Voltage	1500 V	Series Fuse Rating	25 A

BI-FACIAL OUTPUT - BACKSIDE POWER GAIN*

		BiN-05-415	BiN-05-420	BiN-05-425	BiN-05-430	BiN-05-435	BiN-05-440
450/	Power Output (W)	477	483	488	494	500	506
15%	Module Efficiency (%)	24.46%	24.75%	25.04%	25.34%	25.63%	25.91%
000/	Power Output (W)	498	504	510	516	522	528
20%	Module Efficiency (%)	25.52%	25.83%	26.13%	26.44%	26.74%	27.03%
25%	Power Output (W)	518	525	531	537	543	550
	Module Efficiency (%)	26.58%	26.91%	27.22%	27.55%	27.86%	28.16%
30%	Power Output (W)	539	546	552	559	565	572
30%	Module Efficiency (%)	27.65%	27.98%	28.31%	28.65%	28.97%	29.29%

^{*}The bifacial gains are dependant on the power plant design and location

DESIGN SPECIFICATIONS



THERMAL CHARACTERISTICS

Temperature coefficient of Current (Isc), α (%/°C)	0.046	
Temperature coefficient of Voltage (Voc), B (%/°C)	-0.26	
Temperature coefficient of Power (Pm), γ (%/°C)	-0.31	
NOCT (°C)	43 ± 2	
Operating temperature range (°C)	-40 to 85	
Bifaciality Factor (%)	80 ± 5	

MECHANICAL CHARACTERISTICS

	_
Length x Width x Thickness (L x W x T)	1722 mm (L) x 1134 mm (W) x 33 mm (T)
Weight	24.5 kgs
Solar Cells per Module (Units) / Arrangement	108 cells / (9x6 9x6)
Solar Cell Type & Size	TOPCon N-type Mono Bifacial,91x182mm
Front / Back Glass (Material / Thickness)	2.0 mm Low Iron ARC Semi-Tempered glass
Encapsulate	PID Free & UV Resistant
Junction Box (Protection degree / Material)	IP68 / Weatherproof PPO
Cable & Connector (Protection degree / Type)	IP68 rated / MC4 compatible
Cable cross - section & Length	4 mm ² & 500mm
Frame	Anodized Aluminium Alloy

Waaree Energies Ltd. is amongst the top Solar Energy Companies and has the country's largest Solar PV Module manufacturing capacity of 12 GW. In addition, it is committed to provide top notch EPC services, project development, rooftop solutions, solar water pumps and also in an Independent Power Producer. Waaree has its presence in over 350+ locations nationally and 68 countries globally.

12 Years Product Warranty • 30 Years Power Output Warranty

- The electrical data given here is for reference purpose only.
- $\bullet \ \mathsf{Please} \ \mathsf{confirm} \ \mathsf{your} \ \mathsf{exact} \ \mathsf{requirements} \ \mathsf{with} \ \mathsf{the} \ \mathsf{sales} \ \mathsf{representative} \ \mathsf{while} \ \mathsf{placing} \ \mathsf{your} \ \mathsf{order}.$
- Refer installation Manual instructions & Waaree warranty statement for terms & conditions.
- Waaree Reserves the right to change the specifications without prior notice.